

LED Downlights

Thirteen downlight references split between plain recessed fittings and Wi-Fi models that dim and shift colour temperature from a phone, including ultra-thin 9W and 12W round and square bodies.

13 references. Every figure below is reproduced from the manufacturer's own documentation for that reference; where a table is absent, no specification was published.

Dimmable wifi WWCW Ultra-thin Round down light 12W

Wi-Fi Downlights

No specification table was published for this reference. Ask and the current sheet will be emailed.

Dimmable wifi WWCW Ultra-thin Round down light 9W

Wi-Fi Downlights

No specification table was published for this reference. Ask and the current sheet will be emailed.

Dimmable wifi WWCW Ultra-thin Square down light 12W

Wi-Fi Downlights

No specification table was published for this reference. Ask and the current sheet will be emailed.

Dimmable wifi WWCW Ultra-thin Square down light 9W

Wi-Fi Downlights

No specification table was published for this reference. Ask and the current sheet will be emailed.

RGBW 12W - P/N CRDL-WF-03

Wi-Fi Downlights

LED Power	12W
LED Quantity	5630 48PCS
Luminous Flux	1100lm Max
Working Mode	RGBW
Color Adjustable	16million colors changing
Brightness	100lm~1100lm Adjustable
Color Rendering Index	Ra>85
Input Voltage	Input 100~240Vac 50/60Hz
Power Factor	>0.9
Material of case	Aluminum
Life Span	40,000 Hours
Operating Temperature	-25°C to 50°C
Humidity	0~90%
Telecontrol distance	20-30meters
Radio frequency	2.4GHz
Hole Size	125~140mm
Unit Dimension	145X78mm
Inner Box Size	190X190X120mm

WWCW 12W - P/N CRDL-WF-01

Wi-Fi Downlights

LED Power	12W
-----------	-----

LED Quantity	5630 48PCS
Luminous Flux	1100lm Max
Working Mode	CCT & Brightness Adjustable
Color Temperature	2700~6500K Adjustable
Brightness	100lm~1100lm Adjustable
Color Rendering Index	Ra>85
Input Voltage	Input 100~240Vac 50/60Hz
Power Factor	>0.9
Material of case	Aluminum
Life Span	40,000 Hours
Operating Temperature	-25°C to 50°C
Humidity	0~90%
Telecontrol distance	20-30meters
Radio frequency	2.4GHz
Hole Size	125~140mm
Unit Dimension	145x78mm
Inner Box Size	190x190x120mm

WWCW 6W - P/N CRDL-WF-02

Wi-Fi Downlights

LED Power	6W
LED Quantity	5630 24PCS
Luminous Flux	560lm Max
Working Mode	CCT & Brightness Adjustable
Color Temperature	2700~6500K Adjustable
Brightness	60lm~560lm Adjustable
Color Rendering Index	Ra>85
Input Voltage	Input 100~240Vac 50/60Hz
Power Factor	>0.9
Material of case	Aluminum
Life Span	40,000 Hours
Operating Temperature	-25°C to 50°C
Humidity	0~90%
Telecontrol distance	20-30meters
Radio frequency	2.4GHz
Hole Size	78~95mm
Unit Dimension	100X65mm
Inner Box Size	140X140X110mm

led down light 1W

Standard Downlights

No specification table was published for this reference. Ask and the current sheet will be emailed.

led down light 3w

Standard Downlights

No specification table was published for this reference. Ask and the current sheet will be emailed.

led down light 5w

Standard Downlights

No specification table was published for this reference. Ask and the current sheet will be emailed.

led down light 6w

Standard Downlights

No specification table was published for this reference. Ask and the current sheet will be emailed.

led down light 7w

Standard Downlights

No specification table was published for this reference. Ask and the current sheet will be emailed.

led down light 8w

Standard Downlights

No specification table was published for this reference. Ask and the current sheet will be emailed.