

# OHS Series Hyperbaric Chamber

Model OHS Series · specification sheet

Rigid aluminium shell chamber with a 40 mm polycarbonate door, in 1-person and 2-person configurations at 90 kPa.



|                  |                                                        |
|------------------|--------------------------------------------------------|
| Model            | OHS Series                                             |
| Build type       | Hard shell (aluminium alloy)                           |
| Working pressure | 90 kPa maximum                                         |
| Dimensions       | 2000 x 980 x 1700 mm (1P) / 2000 x 1480 x 1700 mm (2P) |
| Capacity         | 1 person or 2 persons                                  |
| Warranty         | 1 year (extendable +2 years)                           |
| Lead time        | 10-30 days (after testing)                             |
| Shipping         | Sea / air freight, worldwide                           |
| MOQ / OEM        | 1 unit, OEM, ODM and colour customise                  |

## Key features

- Rigid aluminum construction
- Spacious upright design
- 40 mm transparent polycarbonate door
- 90 kPa maximum pressure
- 1-person or 2-person configurations
- Electric seating, warm LED lighting

## Overview

The Oxygen Times Shell Hyperbaric Chamber combines a rigid aluminum-alloy Chamber, a large transparent polycarbonate door, spacious interior, and integrated pressure and oxygen systems in a modern enclosed design. Available in single-person and two-person configurations, the Shell Series is designed for users who value comfort, easy access, premium finishing, and dependable everyday operation.

## Technical specifications

| Item             | 1-Person Version             | 2-Person Version             |
|------------------|------------------------------|------------------------------|
| Capacity         | 1 Person                     | 2 Persons                    |
| Dimensions       | 2000 × 980 × 1700 mm         | 2000 × 1480 × 1700 mm        |
| Maximum Pressure | 90 kPa                       | 90 kPa                       |
| Chamber Material | High-Strength Aluminum Alloy | High-Strength Aluminum Alloy |

| Item              | 1-Person Version          | 2-Person Version          |
|-------------------|---------------------------|---------------------------|
| Door              | 40 mm Polycarbonate       | 40 mm Polycarbonate       |
| Front Window      | 350 mm                    | 350 mm                    |
| Rear Window       | 450 mm                    | 450 mm                    |
| Chamber Weight    | Approx. 330 kg            | Approx. 380 kg            |
| Oxygen Output     | 10 L/min                  | 20 L/min                  |
| Seating           | 1 Electric Seat           | 2 Electric Seats          |
| Interior Lighting | Warm LED                  | Warm LED                  |
| Interior Voltage  | 24V                       | 24V                       |
| Pressure Relief   | 2 Automatic + 1 Emergency | 2 Automatic + 1 Emergency |
| Structure         | Separable                 | Separable                 |
| Wheels            | 4 Foma Wheels             | 4 Foma Wheels             |

## Quality control before shipment

- Pressure testing before dispatch
- Airtightness inspection
- Functional performance testing
- Appearance inspection
- Export packaging inspection

## Certifications

TBC — no certificate numbers or issuing bodies are published for this model. Request the current certification position for your market from the factory before ordering.

## Ordering

|               |                                                                                                        |
|---------------|--------------------------------------------------------------------------------------------------------|
| Minimum order | 1 unit, including colour customisation                                                                 |
| Lead time     | 10-30 days after quality testing, confirmed at order                                                   |
| Freight       | Air freight 7-10 days, sea freight 4-6 weeks                                                           |
| OEM / ODM     | Logo, colour, packaging, manuals, accessories, pressure configuration, destination electrical standard |
| Warranty      | 1 year, extendable by 2 further years                                                                  |
| Contact       | sales@o2times.com · WhatsApp +86 180 6880 3928                                                         |

This document describes equipment. It is not medical advice. How a hyperbaric chamber may be used, and by whom, is set by the regulations of the country it is installed in, and meeting them is the buyer's responsibility. No product certification is claimed; values the factory does not publish are marked TBC.